


CPF4N



connectwell
THE RIGHT CONNECTION

4 sq.mm Push in Fuse Terminal Blocks

CP series Push-In Terminal Blocks have a specialised connection system that enables tool less wire connections. Reliable, vibration resistant, gas tight connections are made with inbuilt high quality stainless steel Push in spring clamps.

TECHNICAL DATA

Rated Voltage	1000 V
Rated Current	10 A
Housing Material	Polymide
Standard Colour	Grey
Product Function	Single Level Fuse
Wire Entry Orientation	Top
Mounting Possibility	DIN 35/DIN 35-15 Rail
Rated Surge Voltage	8 KV
Pollution Degree	3

CONNECTION DATA

Conductor Cross Section Stranded min.	0.2 mm ²
Conductor Cross Section Stranded max.	4 mm ²
Conductor Cross Section AWG/Kcmil min	24 AWG
Conductor Cross Section AWG/Kcmil max	10 AWG
Stripping Length	11 mm

DIMENSIONS

Height	69.2 mm
Height with DIN 35 x 15 mm rail	76.25 mm
Height with DIN 35 x 7.5 mm rail	68.75 mm
Length	70.7 mm
Width (Thickness)	6 mm

FUSE SPECIFICATIONS

Fuse Type	Cartridge fuse
Fuse Size	5X20 mm

ORDERING INFORMATION

CAT. NO.	DESCRIPTION	STD. PACK
CPF4N	4 sq.mm Push in Fuse Terminal Block in Grey Colour	50
CPF4NL6-60V	4 sq.mm Push in Fuse Terminal Block with LED (6-60V) in Grey Colour	50
CPF4NL110-240V	4 sq.mm Push in Fuse Terminal Block with LED (110-240V) in Grey Colour	50
CPF4NL110-240VBK	4 sq.mm Push in Fuse Terminal Block with LED (110-240V) in Black Colour	50

ACCESSORIES

IMAGES	CAT. NO.	DESCRIPTION	STD. PACK
	CA701-1M	Din 35 Rail unslotted 1 meter	50
	CA701-2M	Din 35 Rail unslotted 2 meter	50
	CA701-2M-S	Din 35 Rail slotted 2 meter	50
	CA701-1M-S	Din 35 Rail slotted 1 meter	50
	CA701-15-1M	Din 35 Rail 15 deep unslotted 1 meter	50
	CA701-15-1M-S	Din 35 Rail 15 deep slotted 1 meter	50
	CA701-15-2M	Din 35 Rail 15 deep unslotted 2 meter	50
	CA701-15-2M-S	Din 35 Rail 15 deep slotted 2 meter	50
	CA104	EndClamp in Polyamide suitable for Din 35/Din 35-15 rails	50
	CA103	EndClamp in Polyamide suitable for Din 35/Din 35-15 rails	50
	JX4/2	Shorting Link for 6 mm wide TB	100
	JX4/3	Shorting Link for 6 mm wide TB	50
	JX4/4	Shorting Link for 6 mm wide TB	50
	JX4/5	Shorting Link for 6 mm wide TB	50
	JX4/8	Shorting Link for 6 mm wide TB	10
	JX4/10	Shorting Link for 6 mm wide TB	10
	JX4/16	Shorting Link for 6 mm wide TB	10
	MC6	MARKER CARD 6MM PITCH WITH 72 TAGS	10
	SCS0.5/3	Electricians Screwdriver for slotted screws	10


APPROVALS



NOTES

The Rated current is with the use of copper (Cu) conductor/Wire
Flammability Grade V0 as per UL 94

CPF4N



connectwell
THE RIGHT CONNECTION

RATINGS AS PER STANDARDS

STANDARDS	IEC 60947-7-1	UL 1059
Conductor Cross Section Stranded min.	0.2 mm ²	24 AWG
Conductor Cross Section Stranded max.	4 mm ²	10 AWG
Rated Voltage	1000 V	600 V
Rated Current	10 A	10 A