


CPG1.5


connectwell
 THE RIGHT CONNECTION

1.5 sq.mm Push in Feed Through compact Terminal Blocks

These Terminal Blocks have specially designed alloy feet which help in achieving very low contact resistance and vibration proof grounding with the DIN rails. They green/yellow colour coded as industry standards.

TECHNICAL DATA

Rated Voltage	800 V
Rated Current	15 A
Housing Material	Polymide
Standard Colour	Green-Yellow
Product Function	Earthing/Grounding
Wire Entry Orientation	Top
Mounting Possibility	DIN 35/DIN 35-15 Rail
Rated Surge Voltage	8 KV
Pollution Degree	3

CONNECTION DATA

Conductor Cross Section Stranded min.	0.2 mm ²
Conductor Cross Section Stranded max.	1.5 mm ²
Conductor Cross Section AWG/Kcmil min	24 AWG
Conductor Cross Section AWG/Kcmil max	14 AWG
Stripping Length	8 mm

DIMENSIONS

Height with DIN 35 x 15 mm rail	40.3 mm
Height with DIN 35 x 7.5 mm rail	32.8 mm
Length	45.3 mm
Width (Thickness)	3.5 mm

ORDERING INFORMATION

CAT. NO.	DESCRIPTION	STD. PACK
CPG1.5	1.5 sq.mm Earthing Push in Terminal Block in Green-Yellow colour	100

ACCESSORIES

IMAGES	CAT. NO.	DESCRIPTION	STD. PACK
	CA701-1M	Din 35 Rail unslotted 1 meter	50
	CA701-2M	Din 35 Rail unslotted 2 meter	50
	CA701-2M-S	Din 35 Rail slotted 2 meter	50
	CA701-1M-S	Din 35 Rail slotted 1 meter	50
	CA701-15-1M	Din 35 Rail 15 deep unslotted 1 meter	50
	CA701-15-1M-S	Din 35 Rail 15 deep slotted 1 meter	50
	CA701-15-2M	Din 35 Rail 15 deep unslotted 2 meter	50
	CA701-15-2M-S	Din 35 Rail 15 deep slotted 2 meter	50


ACCESSORIES

IMAGES	CAT. NO.	DESCRIPTION	STD. PACK
	CA103	EndClamp in Polyamide suitable for Din 35/Din 35-15 rails	50
	CA104	EndClamp in Polyamide suitable for Din 35/Din 35-15 rails	50
	EPCP1.5	End Plate in Grey Colour	50
	JX1.5/2	Shorting Link for 1.5 sq mm series	100
	JX1.5/3	Shorting Link for 1.5 sq mm series	50
	JX1.5/4	Shorting Link for 1.5 sq mm series	50
	JX1.5/10	Shorting Link for 1.5 sq mm series	10

APPROVALS



CPG1.5



connectwell
THE RIGHT CONNECTION

RATINGS AS PER STANDARDS

STANDARDS	UL 1059	CSA C.22.2 No:158	IEC/EN60947-7-1
Approvals	UL	CSA	CE
Conductor Cross Section Stranded min.	24 AWG	24 AWG	0.2 mm ²
Conductor Cross Section Stranded max.	14 AWG	14 AWG	1.5 mm ²