


CPST1.5/3



connectwell
THE RIGHT CONNECTION

1.5 mm² 3-wire connector for sensor and actuator.

Sensor and Actuator Push in Terminal Block are ideal for wiring modern machine control systems. These are extremely compact and space saving.

TECHNICAL DATA

Rated Voltage	250 V
Rated Current	13.5 A
Housing Material	Polymide
Standard Colour	Grey
Product Function	Select
Wire Entry Orientation	Top
Mounting Possibility	DIN 35/DIN 35-15 Rail
Rated Surge Voltage	4 KV
Pollution Degree	3

CONNECTION DATA

Conductor Cross Section Stranded min.	0.2 mm²
Conductor Cross Section Stranded max.	1.5 mm²
Conductor Cross Section AWG/Kcmil min	24 AWG
Conductor Cross Section AWG/Kcmil max	14 mm²
Stripping Length	8 mm

DIMENSIONS

Height with DIN 32 rail	mm
Height with DIN 35 x 15 mm rail	55.55 mm
Height with DIN 35 x 7.5 mm rail	48.1 mm
Length	79.8 mm
Width (Thickness)	3.5 mm

ORDERING INFORMATION

CAT. NO.	DESCRIPTION	STD. PACK
CPST1.5/3	1.5 sq.mm Sensor and actuator push in Terminal Block in Grey colour	50
CPST1.5/3L6-60V	1.5 sq.mm Sensor and actuator push in Terminal Block in Grey colour	50
CPST1.5/3L110-240V	1.5 sq.mm Sensor and actuator push in Terminal Block in Grey colour	50

ACCESSORIES

IMAGES	CAT. NO.	DESCRIPTION	STD. PACK
	CA701-1M	Din 35 Rail unslotted 1 meter	50
	CA701-2M	Din 35 Rail unslotted 2 meter	50
	CA701-2M-S	Din 35 Rail slotted 2 meter	50
	CA701-1M-S	Din 35 Rail slotted 1 meter	50

ACCESSORIES

IMAGES	CAT. NO.	DESCRIPTION	STD. PACK
	CA701-15-1M	Din 35 Rail 15 deep unslotted 1 meter	50
	CA701-15-1M-S	Din 35 Rail 15 deep slotted 1 meter	50
	CA701-15-2M	Din 35 Rail 15 deep unslotted 2 meter	50
	CA701-15-2M-S	Din 35 Rail 15 deep slotted 2 meter	50
	CA103	EndClamp in Polyamide suitable for Din 35/Din 35-15 rails	50
	MS3.5	Marking Tag Blank suitable for 3.5mm Terminal Blocks	100
	JX1.5/2	Shorting Link for 1.5 sq mm series	100
	JX1.5/3	Shorting Link for 1.5 sq mm series	50
	JX1.5/4	Shorting Link for 1.5 sq mm series	50
	JX1.5/10	Shorting Link for 1.5 sq mm series	10
	EPCPPT2.5/3	End Plate for CPST and CPPT	50
	MC3.5	MARKER CARD 3.5MM PITCH WITH 120 TAGS	10


APPROVALS



NOTES

The Rated current is with the use of copper (Cu) conductor/Wire

CPST1.5/3



connectwell
THE RIGHT CONNECTION

RATINGS AS PER STANDARDS

STANDARDS	UL 1059	CSA C.22.2 No:158	IEC/EN60947-7-1
Approvals	UL	CSA	CE
Conductor Cross Section Stranded min.	24 AWG	24 AWG	0.2 mm ²
Conductor Cross Section Stranded max.	14 AWG	14 AWG	1.5 mm ²
Rated Voltage	150 V	150 V	250 V
Rated Current	15 A	15 A	13.5 A