


Gen Next Led Holder



Voltage	Part No.	Part No.	Part No.	Part No.	Part No.	Part No.
						
12V AC/DC	EG08H0LR012C	EG08H0LG012C	EG08H0LB012C	EG08H0LY012C	EG08H0LA012C	EG08H0LW012C
24V AC/DC	EG08H0LR024C	EG08H0LG024C	EG08H0LB024C	EG08H0LY024C	EG08H0LA024C	EG08H0LW024C
30V AC/DC	EG08H0LR030C	EG08H0LG030C	EG08H0LB030C	EG08H0LY030C	EG08H0LA030C	EG08H0LW030C
48V AC/DC	EG08H0LR048C	EG08H0LG048C	EG08H0LB048C	EG08H0LY048C	EG08H0LA048C	EG08H0LW048C
64V AC/DC	EG08H0LR064C	EG08H0LG064C	EG08H0LB064C	EG08H0LY064C	EG08H0LA064C	EG08H0LW064C
110V AC	EG08H0LR110A	EG08H0LG110A	EG08H0LB110A	EG08H0LY110A	EG08H0LA110A	EG08H0LW110A
110V DC	EG08H0LR110D	EG08H0LG110D	EG08H0LB110D	EG08H0LY110D	EG08H0LA110D	EG08H0LW110D
240V AC	EG08H0LR240A	EG08H0LG240A	EG08H0LB240A	EG08H0LY240A	EG08H0LA240A	EG08H0LW240A
220V DC	EG08H0LR220D	EG08H0LG220D	EG08H0LB220D	EG08H0LY220D	EG08H0LA220D	EG08H0LW220D

LED Holder



Test Parameters	Specification
Product	Gen Next LED Actuators
Rated Voltage	12 V AC/DC, 24 V AC/DC, 30 V AC/DC, 48 V AC/DC, 64 V AC/DC, 110 V AC, 110 V DC, 240 V AC, 220V DC
Operating Voltage	-20% to +10% of rated voltage
Type of LED	Side View SMD LED's
Available Colours	Red / Green / Yellow / Amber / Blue / White
Life / Warranty	0.1 Million burning hours/24 Months**
Operating Frequency	50 / 60 Hz
Operating Temperature	-25°C to 65°C
Storage Temperature	-30°C to 70°C
Wire Termination Capacity	0.5 mm ² , 1.5 - 2.5 mm ²
Terminal Torque	0.8 Nm
LVGP	Available
Surge Test	2KV
HV test for 60 sec.	1.5KV
Degree of Protection	Above Panel: IP65 For Terminals: IP20
International Approvals	CE, UL

**To be used only with Gen Next Contact Blocks & Gen Next LED holder.